

REVISIONS				
REV	ECN	DESCRIPTION	DATE	BY

SPECIFICATION:

Electrical:

- Current Rating:1.5Amp MAX. 68℃
- Voltage Rating:180VAC MAX.
- Insulation Resistance:500 Megohms MIN.
- Contact Resistance:20 milliohms MAX. (Initial)
- Withstanding Voltage:
Contact to Contact: 1,000 VDC or AC Peak for 1 minute

Mechanical:

- Operating Temperature:-40 ℃~+65℃
- Storage Temperature: -40 ℃~+65℃
- Durability: 750 Mating Cycles MIN.

Material:

- Housing:Thermoplastic UL94V-0
- Insert:Thermoplastic UL94V-0
- Contact:T=0.35mm Phosphor Bronze C5210

Wave Soldering: 230+/-5℃,5 sec max;
Resistance to solder : 230+/-5℃,10 +/- 1sec
packaging: Tray

Part No.: PJ-C1-FG20-EA011-7

P:8Point 8Contact	Plating Gold 7:Pa*
Plastic Material G:PBT (UP)	A011: 金鍍无灯, 中心高7.94mm
Plastic Color BLUE (205C)	E 金鍍 HTC mark

TOLERANCE		SIGNATURES		DATE	HUNTER 東莞行特電子有限公司
ANGLE	±0.5°	DESIGN:	David	2024-02-19	
.X	±0.25	CHECKED:	David	2024-02-19	
.XX	±0.15	APPROVAL:	Andy	2024-02-19	
.XXX	±0.10	SHEET	SCALE	UNIT	REV
1 OF 1				mm	A/01
TITLE					RJ45 8P8C SINGLE PORTS
PART NO.					PJ-C1-FG20-EA011-7